



AUTOMATED STOP & POSITIONER 300-600 CM

ASP

ASP-3 : 3 Metre

ASP-3S : 3 Metre, Servo Motor

ASP-6 : 6 Metre

ASP-6S : 6 Metre, Servo Motor



» General Features ASP-3 and ASP-6

- Works with machines of any brand
- PLC Windows CE Operation System
- Memory: up to 1,200 cut lists memory for use with optimization system. Up to 5,000 cut lists memory if no optimization system is used
- It is a PLC controlled conveyor. It helps to cut the window glass profile path to the desired dimensions precisely in the cutting machines
- Manual or automatic operation
- 10" touch screen
- Manual or computer recipe creation
- Data transfer with usb flash disk
- Possibility to change the cutting list on the screen
- Production in special dimensions according to demand

✓ Standard

- Right

○ Optional

- Custom clamp fixture for profile
- Transfer cut list with USB stick
- Connection to the left side of the machine





» ASP-3S and ASP-6S

(In addition to the above)

- Data transfer via wifi
- Technical support via remote connection
- Laser meter and Bluetooth



» Teknik Tablo

 Servo kW	 Packing Size	 Machine Size	 Machine Kg
ASP-3 : 0,25 kW, 220 V, 50/60 Hz ASP-3S : 1x0.75 kW	W x L x H (cm) ASP-3/3S: 316x53x59 cm	W x L x H (cm) ASP-3/3S: 300x66x153 cm	115

